Toyota HiAce 15S Minibus DLX STD Roof

Technical details:

| KDH202L-REMDYV |
|--|
| Japan |
| Diesel, 2,494 cc, 4-cyl. in-line 16V DOCH, |
| solenoid fuel injection, Common Rail |
| 101 HP w/3600 rpm, 26.5 KgM/1600-2400 |
| rpm 5-speed manual (floor) |
| 195R15 tire, 15" steel wheel |
| Ventilated Disc/Rear Drum w/LSPV |
| Heavy duty. |
| Front: Independent double wishbone, |
| Rear: leaf spring |
| 15 seats, Upholstery: Fabric |
| 70L |
| |

Standard Equipment:

- Power/tilt steering
- Side impact beam
- Bumper front and rear, black
- Green laminated windshield
- High mount stop lamp
- Outer mirrors, black
- Door handles, black
- Fuel lid opener
- Front seat belts 3PELRx2+2PNRx1
- Rear seat belts 2PNRx12
- Digital clock
- Inner rear view mirror day/night
- Sun visor driver/passenger
- Wiper front intermittent
- Meter illumination control
- Antenna and 2 speakers
- Dual air-conditioner, manual front and rear
- Front heater/demister

• Dimension & Weight

- LWH : 4695 x 1695 x 1980 mm
- Wheelbase : 2570 mm
- Curb Weight : 1870 kg
- Gross Vehicle Weight : 3000 kg
- Ground clearance: 235 mm

NB! Specifications are subject to change without further notice and to be confirmed upon ordering